

Mayco C30HDGA Small Line Concrete Pump

Mayco's C30HDGA has been in production for over 54 years and is still the most popular small line concrete pump available today.

This versatile piston pump will easily handle up to ½ inch minus aggregate and pump up to 25 cubic yards per hour. The C30HDGA handles a variety of mix designs including harsh, stiff and low slump mixes.

A direct flow manifold with oversized valves assures maximum volume and minimizes the chance of blockages and cavitation.


The C30HDGA is engineered to require only minimal maintenance and upkeep. All components are manufactured from the highest quality materials and built to exacting specifications to maximize service life.

Service is simplified by a central lubrication system that enables the operator to quickly grease every critical service point. A fully enclosed lube box provides positive lubrication and can be easily cleaned out.

Mayco replacement parts are reasonably priced and readily available. Additionally, our nationwide network of dealers is ready to provide service and technical support no matter where your job is located.

The C30HDGA is ideal for shotcrete applications of stiff, low slump mixes — swimming pools, ditch linings, soil stabilization, walls and more.

C30HDGA
*Up to 25 yd.³
per hour*



www.ConcreteEquipmentInc.com



PERFORMANCE

Max volume output25 yards³/hr (19m³/hr)
Max concrete pressure500 psi (35 bar)
Max aggregate size1/2" minus (-12mm)

SPECIFICATIONS

Type ..Mechanical Drive, Ball & Seat Reciprocating Pump w/Accumulator Piston
Concrete cylinders.....6" x 12" (152x305mm)
Strokes per minute..... 135
Volume controlAdjustable, 3-Position
Hopper height.....52" (1321mm)
Hopper capacity6 ft³ (170L)
Outlet diameter3" HD (76mm)

ENGINE

ManufacturerZenith (Hyundai)
Model.....Z416-Gamma
TypeGasoline Fuel Injection
Horsepower45 (33.6kW)
Fuel tank capacity 11 US gal (42L)

TRAILER

Axle capacity.....3500 lb (1588kg)
Tires/Load range.....ST205/75D14
Hitch2" Ball Coupler (Ball Not Included)

DIMENSIONS

Length144" (366 cm)
Width59" (149 cm)
Height.....64" (164 cm)
Weight (approximate).....2910 lbs (1320 kg)

Maximum theoretical values listed above. Maximum output and pressure cannot be achieved simultaneously.

Note: Specifications subject to change without notice.

MQ/Mayco assumes no liability for the merchantability of any piece of equipment to perform a specific job. The applicability of a specific pump or placing system for a particular application is the sole responsibility of the purchaser.

CONCRETE EQUIPMENT

STANDARD FEATURES

- (1ea) Elbow, 3" HD x 3" HD x 90°
- (1ea) Reducer, 3" HD x 2" HD x 36"
- (2ea) Clamps, 3" HD
- High Performance Gasoline Engine
- Rugged Steel Hood w/Safety Switch
- Single-Piece Forged & Hardened Crankshaft
- Fully Enclosed Piston Lubrication Box
- Hard Chromed Concrete Cylinders
- Remote Bearing Lubrication System
- Hinged E-Z Open Manifold & Exhaust Cone
- 3-Position Primary Piston Stroke
- Heavy Duty Frame w/Torsion Suspension
- Under Slung, In-Frame Fuel Tank
- Diagnostic Control Panel w/Engine Hour Meter
- Automatic Engine Throttle Control on the Panel
- On/Off Remote Control w/125' (39.7m) Cable
- Fenders & Tail Lights
- Adjustable Front Jack Stand
- Manual Rear Outrigger
- High Quality Powder Finish – Yellow & Gray
- Warranty: 1-Year Pump (MQ), 2-Year or 2,000 Hours Engine (Zenith)

OPTIONS: Not Included in Net Selling Price.

- 1) Wireless Remote 3-function, 800' range, (On/Off/Volume)\$2,125.00
- 2) Screen Vibrator, Air\$560.00
- 3) Ball Hitch, 2-5/16"\$130.00
- 4) Pintle Tow Ring, 3"\$130.00



CONCRETE EQUIPMENT Support@ConcreteEquipmentInc.com 858-775-7800

www.ConcreteEquipmentInc.com