

PUMP BOSS™

PUMP BOSS III REMOTE CONTROL



HIGHLIGHTS

- Increases productivity and safety for concrete pump operators
- Rugged and reliable system using the latest generation design
- Long-range 2.4GHz radio system with more than 600ft of operating range
- Closed box configuration and diagnostics over Bluetooth®

FEATURES

- Eight solid state outputs 2 X 10A, 6 X 4A in a Category 3 PL-d configuration
- Single CANbus interface that supports J1939 and CANopen
- Wide range 9-36 VDC supply designed to meet tough mobile application requirements
- Frequency and address management are not required
- Simple pushbutton configuration of spares
- High EMI performance in tough environments
- Leather holster included
- One-year warranty

APPLICATIONS

- Concrete mixer trucks
- Volumetric concrete mixer trucks
- Concrete line pumps
- Vacuum trucks





TECHNICAL DATA AND SPECIFICATIONS

ELECTRONIC DATA	
Digital Circuitry	Dual 32-bit microcontrollers
System Address	48-bit MAC and 24 Bit Master
Power Requirements	MCU: 9-36 VDC OCU: two 1.5V AA Alkaline batteries or a LiPo rechargeable option

RF	
Frequency	License exempt: 2.4GHz
Connection	Two SMA supporting antenna diversity
Antennas	Chassis mount (standard) or Mag-mount (option)
Telegram	Dynamic high-efficiency telegram
Data Security	Enhanced black channel communication

MCU INTERFACES	
Power	9-36 VDC 20W
Digital Out	Eight solid state PL-d outputs 2 X 10A, 6 X 4A (36 VDC max)
CAN	One CAN port supporting J1939, CANopen
Harness	MCU is supplied with a 6ft cable assembly for power, digital and CAN
Bluetooth	Supporting OTA diagnostics, programming and configuration

MECHANICAL DATA	
Enclosure	MCU: aluminum / OCU: fiber-reinforced nylon
Weight	OCU: 9 oz (250g) MCU: 1.8 lbs (816g)
Dimensions	MCU: 2x8x6in. (50x200x150mm) OCU: 6.5x2.8x1in. (165x71x25mm)
Operating Temperature	-4° to +140°F (-20° to +60° C)
Shock Resistance	MCU: 17G OCU: 1m drop onto concrete
IP Protection Class	MCU: IP66 / OCU: IP65

COMPLIANCE	
ISO 16750-1/-3/-4	Environmental
ISO 7637-2/-3	Electrical disturbances
ISO 13766	Electromagnetic compatibility
EN60204-1	Safety of machinery – electrical equipment
EN ISO 13849	Functional safety category 3 PL-d
RF Compliance	Approved in all regions of sale per national and regional requirements
ISO 11898-2	CANbus fault protection

ACCESSORIES	
Antenna	Chassis mount and line kit or Magnet mount and line kit
Battery Charger	Drop-in cradle and power adapter, various power options available
Rechargeable Battery	LiPo rechargeable battery
Leather Holster	For OCU

North America: +1.234.806.0018 | Sales.US@Cattron.com

Europe: +49.2151.4795.0 | Sales.EU@Cattron.com

UK: +44.1932.238121 | Sales.UK@Cattron.com

South America: +55.19.3518.7030 | Sales.BR@Cattron.com

Asia: Sales.CN@Cattron.com

Oceania: Sales.AU@Cattron.com

cattron.com

EN-2023-06-V1

Cattron™ reserves the right to change specifications and product details on this datasheet without prior notice. Cattron and all associated logos or marks are trademarks of Cattron and/or its subsidiaries. All rights reserved.